STRIP LIGHTING FIXTURE 9256

Ceiling lights

PRODUCT DESCRIPTION

■ extruded profile and end caps of aluminium, powder coated ■ top: aluminium ceiling fastener, powder coated ■ bottom: stanchion, aluminium, powder coated ■ indirect light emission clearly covered by polycarbonate profile with brinelled structure ■ entrance areas and housing ends with halogen spots or LED spots in chrome ■ internal wiring and free cable ends halogen-free line ■ type Radox Huber + Suhner, connection on WAGO-clamps, series 261, 2,5 mm² ■ solid construction, protection against vandalism ■ fire prevention DIN 5510 or DIN EN 45545, system of protection IP20 ■ type 9256-40 and 9256-400 consists of two components ■ special designs on request



DIMENSION DRAWING



PRODUCT DETAILS

CODE	LAMP	WATTS (W)	BALLAST	WEIGHT (KG)	A (MM)	B (MM)	C (MM)	D (MM)	E (MM)	DESIGN
9256-40	7 T16 39W (indirekt) 4 QR-CB35 20W (direkt)	273/80	TVG 24V DC	51,0	7077	350	150			
9256-50	3 T16 39W (indirekt) 2 QR-CB35 20W (direkt)	117/40	TVG 24V DC	23,0	3151	350	150			
9256-400	7 T16 39W (indirekt) 4 LED-spot 3,5W (direkt)	273/14	TVG 24V DC	51,0	7077	350	150			
9256-515	7 T16 39W (indirekt) 2 LED-spot 3,5W (direkt)	117/7	TVG 24V DC	23,0	3151	350	150			

VARIALUX GmbH · Kleinwolmsdorfer Straße 16 · 01477 Arnsdorf · Phone: (0049) 035 200/27 200 , 27 227 · Fax: (0049) 035 200/27 214 , 27 294 · E-Mail: kontakt@varialux.de