

5126


Wall lights

PRODUCT DESCRIPTION


■ direct luminosity ■ housing and perforated plate coated in RAL 9010 ■ semi-cylindrical acrylic cover respectively glass cover ■ different colours on request ■ symmetrical distribution of luminous intensity ■ protection class I, system of protection IP 20 ■ special design on request



DIMENSION DRAWING



LIGHT CURVE



PRODUCT DETAILS

CODE	LAMP	WATTS (W)	LIGHT FLUX	SOCKET	BALLAST	WEIGHT (KG)	A (MM)	B (MM)	C (MM)	D (MM)	E (MM)	DESIGN
WALL LUMINAIRE WITH ACRYLIC COVER, OPAL												
5126-01-001	1 TC-DE 26 W	26	1800	G24q-3	elec. ballast	1,7	240	206	140	180	40	with wall connecting box
5126-01-002	1 TC-DE 26 W	26	1800	G24q-3	elec. ballast	1,4	240	206	110			without wall connecting box
5126-01-003	2 TC-DE 26 W	52	3600	G24q-3	duo elec. ballast	1,7	240	206	140	180	40	with wall connecting box
5126-01-004	2 TC-DE 26 W	52	3600	G24q-3	duo elec. ballast	1,4	240	206	110			without wall connecting box
5126-01-005	4 LED 4000K	13	2200	LED	LED driver	1,7	240	206	140	180	40	with wall connecting box
5126-01-006	4 LED 4000K	13	2200	LED	LED driver	1,4	240	206	110			without wall connecting box
5126-05-001	1 TC-L 36 W	36	2900	2G11	elec. ballast	4,5	500	206	140	180	40	with wall connecting box
5126-05-002	1 TC-L 36 W	36	2900	2G11	elec. ballast	4,2	500	206	110			without wall connecting box
5126-05-003	2 TC-L 36 W	72	5800	2G11	duo elec. ballast	4,8	500	206	140	180	40	with wall connecting box
5126-05-004	2 TC-L 36 W	72	5800	2G11	duo elec. ballast	4,5	500	206	110			without wall connecting box
5126-05-005	6 LED 6 W	36	5100	LED	LED driver	4,5	500	206	140	180	40	with wall connecting box
5126-05-006	6 LED 6 W	36	5100	LED	LED driver	4,2	500	206	110			without wall connecting box
5126-10-001	2 TC-L 36 W	72	5800	2G11	duo elec. ballast	7,5	1000	206	140	180	40	with wall connecting box
5126-10-002	2 TC-L 36 W	72	5800	2G11	duo elec. ballast	7,2	1000	206	110			without wall connecting box
5126-10-003	4 TC-L 36 W	144	11600	2G11	duo elec. ballast	7,8	1000	206	140	180	40	with wall connecting box
5126-10-004	4 TC-L 36 W	144	11600	2G11	duo elec. ballast	7,5	1000	206	110			without wall connecting box
5126-10-005	6 LED 8 W	48	6180	LED	LED driver	7,5	1000	206	140	180	40	with wall connecting box
5126-10-006	6 LED 8 W	48	6180	LED	LED driver	7,2	1000	206	110			without wall connecting box
WALL LUMINAIRE WITH OPAL GLASS COVER												
5126-15-001	1 TC-DE 26 W	26	1800	G24q-3	elec. ballast	1,8	240	206	140	180	40	with wall connecting box
5126-15-002	2 TC-DE 26 W	52	3600	G24q-3	duo elec. ballast	1,8	240	206	140	180	40	with wall connecting box
5126-15-003	4 LED 4000K	13	2200	LED	LED driver	1,8	240	206	140	180	40	with wall connecting box