

ARTHUR 5290


Ceiling lights / Wall lights

PRODUCT DESCRIPTION


 direct luminosity
  round housing, coated in RAL 9010
  round acrylic cover, convex, opal, satin-frosted
  chromed decorative screws
 symmetrical distribution of luminous intensity
  protection class I, system of protection IP 20
  special design on request



DIMENSION DRAWING



LIGHT CURVE



PRODUCT DETAILS

CODE	LAMP	WATTS (W)	LIGHT FLUX	SOCKET	BALLAST	WEIGHT (KG)	A (MM)	B (MM)	C (MM)	D (MM)	E (MM)	DESIGN
CEILING/ WALL LIGHT Ø 270MM												
5290-01-001	1 TC-F 24W	24	1700	2G10	elec. ballast	1,8	270	100				
5290-01-002	1 TC-DE 18W	18	1200	G24q-2	elec. ballast	1,8	270	100				
CEILING / WALL LIGHT Ø 350MM												
5290-02-001	1 TC-F 36W	36	2800	2G10	elec. ballast	2,0	350	110				
5290-02-002	2 TC-DE 18W	36	2400	G24q-2	duo elec. ballast	2,0	350	110				
5290-02-003	2 TC-DE 26W	52	3600	G24q-3	duo elec. ballast	2,0	350	110				
CEILING /WALL LIGHT Ø 400MM												
5290-03-001	2 TC-F 36W	72	5600	2G10	duo elec. ballast	2,2	400	110				