

SQUARE 1764


Ceiling lights / Wall lights

PRODUCT DESCRIPTION


■ direct luminosity ■ housing coated in RAL 9010 ■ frame and decorative plates V2A, polished ■ symmetrical distribution of luminous intensity
 ■ protection class I, system of protection IP 20 ■ special design on request



DIMENSION DRAWING



LIGHT CURVE



PRODUCT DETAILS

CODE	LAMP	WATTS (W)	LIGHT FLUX	SOCKET	BALLAST	WEIGHT (KG)	A (MM)	B (MM)	C (MM)	D (MM)	E (MM)	DESIGN
CEILING/ WALL LUMINAIRE SQUARE												
1764-01-001	4 TC-L 36W	144	11600	2G11	duo elec. ballast	7,2	622	622	100			sur/rec laminated safety glass with matt finished transparency
1764-01-002	4 TC-L 36W 1 QR-C51 50W	144	11600	2G11/GU5,3	duo elec. ballast	7,2	622	622	100			sur/rec laminated safety glass with matt finished transparency
1764-02-001	1 TC-F 36W	36	2800	2G10	elec. ballast	5,7	390	390	103	350	350	surface - acrylic cover, opal
1764-02-002	2 TC-F 36W	72	5600	2G10	duo elec. ballast	6	390	390	103	350	350	surface - acrylic cover, opal
1764-02-003	5 LED 6W	30	3950	LED	LED driver	5,7	390	390	103	350	350	surface - acrylic cover, opal
1764-03-001	1 TC-F 36W	36	2800	2G10	elec. ballast	5,8	390	390	103	350	350	surface - opal glass cover
1764-03-002	2 TC-F 36W	72	5600	2G10	duo elec. Ballast	6,1	390	390	103	350	350	surface - opal glass cover
1764-03-003	5 LED 6W	30	3950	LED	LED driver	5,8	390	390	103	350	350	surface - opal glass cover