

5238


Pendant lights

PRODUCT DESCRIPTION


■ all-round luminosity ■ spherical, available in 3 different diameters,
 ■ white opal, matt, in shock-resistant plastic, UV-stabilised ■ optional
 glass opal matt or shiny opal ■ ceiling cover, cable or pendant rod
 and spherical cover in white ■ different colours on request ■ rotationally-symmetrical
 distribution of luminous intensity ■ protection class I, system of protection
 IP 20 ■ special design on request



DIMENSION DRAWING



LIGHT CURVE



PRODUCT DETAILS

CODE	LAMP	WATTS (W)	LIGHT FLUX	SOCKET	BALLAST	WEIGHT (KG)	A (MM)	B (MM)	C (MM)	D (MM)	E (MM)	DESIGN
PENDANT LIGHT BALL 300MM												
5238-01-001	2 TC-DE 26W	52	3600	G24q-3	2 elec. ballast	2,6	300	1700				pendant cord with steel core white
5238-01-002	max. 77W	max. 77	1320	E27	-	1,7	300	1700				pendant cord with steel core white
5238-01-003	4 LED 6W	24	4400	LED	LED driver	2,8	300	1700				pendant cord with steel core white
5238-02-001	2 TC-DE 26W	52	3600	G24q-3	2 elec. ballast	2,8	300	1700				pendant rod white
5238-02-002	max. 77W	max. 77	1320	E27	-	1,9	300	1700				pendant rod white
5238-02-003	4 LED 6W	24	4400	LED	LED driver	3,0	300	1700				pendant rod white
PENDANT LIGHT BALL 400MM												
5238-05-001	2 TC-DE 26W	52	3600	G24q-3	duo elec. ballast	3,2	400	1800				pendant cord with steel core white
5238-05-002	3 TC-DE 26W	78	5400	G24q-3	duo elec. ballast/ballast	3,8	400	1800				pendant cord with steel core white
5238-05-003	4 TC-DE 26W	104	7200	G24q-3	2 duo elec. ballast	4,2	400	1800				pendant cord with steel core white
5238-05-004	max. 116W	max. 116	2135	E27	-	2,2	400	1800				pendant cord with steel core white
5238-05-005	9 LED 5W	45	4950	LED	LED driver	3,4	400	1800				pendant cord with steel core white
5238-06-001	2 TC-DE 26W	52	3600	G24q-3	duo elec. ballast	3,4	400	1800				pendant rod white
5238-06-002	3 TC-DE 26W	78	5400	G24q-3	duo elec. ballast/ballast	4,0	400	1800				pendant rod white
5238-06-003	4 TC-DE 26W	104	7200	G24q-3	2 duo elec. ballast	4,4	400	1800				pendant rod white
5238-06-004	max. 116W	max. 116	2135	E27	-	2,4	400	1800				pendant rod white
5238-06-005	9 LED 5W	45	4950	LED	LED driver	3,6	400	1800				pendant rod white
PENDANT LIGHT BALL 450MM												
5238-07-001	4 TC-DE 18W	72	4800	G24q-2	2 duo elec. ballast	4,6	450	1850				pendant cord with steel core white
5238-07-002	2 TC-DE 26W	52	3600	G24q-3	duo elec. ballast	4,4	450	1850				pendant cord with steel core white
5238-07-003	4 TC-DE 26W	104	7200	G24q-3	2 duo elec. ballast	4,6	450	1850				pendant cord with steel core white
5238-07-004	max. 116W	max. 116	2135	E27	-	2,6	450	1850				pendant cord with steel core white
5238-07-005	6 LED 8W	48	6600	LED	LED driver	3,6	450	1850				pendant cord with steel core white
5238-08-001	4 TC-DE 18W	72	4800	G24q-2	2 duo elec. ballast	4,8	450	1850				pendant rod white
5238-08-002	2 TC-DE 26W	52	3600	G24q-3	duo elec. ballast	4,6	450	1850				pendant rod white
5238-08-003	4 TC-DE 26W	104	7200	G24q-3	2 duo elec. ballast	4,8	450	1850				pendant rod white
5238-08-004	max. 116W	max. 116	2135	E27	-	2,8	450	1850				pendant rod white
5238-08-005	6 LED 8W	48	6600	LED	LED driver	3,8	450	1850				pendant rod white